



Typical Performance Characteristics in 25°C Ambient



— center of 3rd shelf — amb temp



center of 3rd shelf

Parameter	W0	W1	W2	W3	H0	H1	D0	D1	D2	
Model	DW-86L729	1049	946	766	750	1980	1310	980	716	710

KEY
W0 --- TOTAL WIDTH
W1 --- FREEZER WIDTH
W2 --- INNER CABINET WIDTH
W3 --- SHELF WIDTH
D0 --- TOTAL DEPTH
D1 --- INNER CABINET DEPTH
D2 --- SHELF DEPTH
H0 --- TOTAL HEIGHT
H1 --- INNER CABINET HEIGHT

Specifications



DW-86L729					
Technical Data	Cabinet Type	Upright	Functions	High/Low Temperature	Y
	Climate Class	N		Hot Condenser	Y
	Cooling Type	Direct Cooling		Power Failure	Y
	Defrost Mode	Manual		High/Low Voltage	Y
	Refrigerant	HC		Sensor Error	Y
	Sound Level (dB(A))	52		Low Battery	Y
Performance	Cooling Performance (°C)	-86	Accessories	High Ambient Temperature	Y
	Temperature Range (°C)	-40~-86		Door Ajar	Y
Control	Controller	Microprocessor	Certification	Caster	Y
	Display	LCD Touchscreen		Foot	Y
Electrical Data	Power Supply (V/Hz)	220~240/50	Porthole	Y/2	
	Electrical Current (A)	9	Shelves/Inner Doors	3/4	
	Power Consumption (kWh/24h)	10	USB Interface	Y	
Dimensions	Capacity (L/Cu.Ft)	729/25.75		Remote Alarm	Y
		Net/Gross Weight (approx)	kg	350/385	5V Power Supply Port
	Interior Dimension (W*D*H)		mm	766*716*1310	Temperature Chart Recorder
		in	30.2*28.2*51.6	RS485 Port	Y
	Exterior Dimension (W*D*H)	mm	1049*980*1980	CO ₂ Backup System	Optional
		in	41.3*38.6*78.0	LN ₂ Backup System	Optional
	Packing Dimension (W*D*H)	mm	1120*1090*2130	CE	Y
		in	44.1*42.9*83.9	Energy Star	Y
Container Load (20'/40'/40'H)		10/22/22			

*Haier Biomedical reserves the right to change products and specifications without prior notice.



DW-86L729

ULT Freezer

Making Your Lab More Intelligent and Reliable

Intelligent Inventory Management
10-inch touchscreen with single version inventory management allows users to easily record item locations, entry and exit records for intelligent stock management.

Safe and Reliable Storage
Temperature uniformity $\pm 4^{\circ}\text{C}$, equipped with an intelligent temperature monitoring system, real-time temperature data monitoring function and multiple safety alarm system.

Energy Saving and Environmentally Friendly
The optimized hydrocarbon refrigeration system is more environmentally friendly and uses significantly less energy than older technologies, saving up to 30% on electricity. ENERGY STAR certified.

Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone, Qingdao, 266109, P.R. China
E-mail: inquiry@haierbiomedical.com
Website: www.haiermedical.com



Ergonomic Design



Narrow Door Design

The freezer can pass through a 880mm wide door when the freezer door is open.



New Handle Design

Adopting exclusive slide design, easy to open and close the door



Pressure Equalization Port

Equipped with pressure equalization port for easy opening



Porthole

Two portholes as standard, allows for independent testing of cabinet temperature



Filter Design

Tool-free removable filter, making it easy and quick to clean the filter



Detachable Inner Door Design

Tool-free detachable inner door, ensuring easy and quick defrost



Product Advantages




Large Intelligent LCD Screen Visual Management

10-inch high-performance LCD capacitive screen, sensitive touch operation; intuitive display of inside temperature, ambient temperature, input voltage and other data and temperature curves.

Stored Items(materials) Management System

An accurate stored items management system was developed for users who don't use freezer racks, boxes and vials, the system easily records the items locations, entry and exit records and largely facilitate item inventory and statistics.



Single version (standard)



Professional version (optional)

The stored item management system was developed for users who use freezer racks, boxes and vials, the system can easily record the item locations, entry and exit records, facilitate item inventory and statistics with multi-screen interaction and reduce errors through secondary verification.

Equipped with Multiple Interfaces

- Standard USB interface, capable of storing data for 10 years
- Standard remote alarm terminal and RS485 port



Multiple Options for Safe Management and Control Systems

Password lock as standard with optional fingerprint module, face recognition and punch card system. Multi-person management control option to ensure safe and secure storage.




Optional IoT System Real-time Monitoring

The IoT APP can monitor the operating status of the equipment anytime and anywhere. The unit is equipped with self-diagnose system faults and alarm functions, ensuring sample safety.



Safe and Secure with Multiple Alarms

Designed and manufactured with multiple alarm functions, such as high temperature alarm, low temperature alarm, sensor failure alarm, power failure alarm, low battery alarm, door ajar alarm and high ambient temperature alarm to name a few.



Precise Temperature Control ensures Safe Storage

The setting temperature is adjustable between -40 ~ -86°C, monitoring temperature curves in real time, and the temperature safety alarm system is the latest design and state-of-the-art technology.