

# -40°C Smart Frequency Conversion Freezer

## DW-40L959BPT



### Scope of Application:

Used in the blood banks, hospitals, disease control centers, research institutes, electronic, chemical and other industries, cryopreservation of plasma, biologics and other products, and cold tests for components and materials.



#### Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,  
Qingdao, 266109, P.R. China  
E-mail: [inquiry@haierbiomedical.com](mailto:inquiry@haierbiomedical.com)  
Website: [www.haiermedical.com](http://www.haiermedical.com)



Haier Biomedical  
International



Haier Biomedical  
International



@haiermedicalint



Haier Biomedical  
International



Haier Biomedical  
International



## Product Features



### High-efficiency and Energy-saving Compressor and System

Optimized refrigeration system with a high efficiency inverter compressor to reduce energy consumption.



### Low Sound Level

Noise level less than 42dB, providing a more comfortable environment.



### Intelligent Control

10-inch high-performance touch screen, sensitive touch operation. Users can check the real-time operating status



### Green and Environmental Friendly

Hydrocarbon refrigerant, energy saving and environmental protection, built with urethane foam insulation complies with European ROHS regulation.



### Superior Temperature Uniformity

The temperature uniformity is  $\pm 3^{\circ}\text{C}$  with the setting temperature of  $-40^{\circ}\text{C}$ .

## Ergonomic Design



### Microprocessor-controlled System

Microprocessor control, with temperature display precision at  $0.1^{\circ}\text{C}$ . Internal temperature is adjustable from  $-20^{\circ}\text{C}$  to  $-40^{\circ}\text{C}$ .



### Super-large Capacity

Large capacity (700 2-inch box) to accommodate the multiple storage needs.



### Safe and Secure

Equipped with key lock, padlock, optional electronic lock, providing multiple safeguards for sample safety.



### Multiple Alarm Functions

Including high/ low temperature, sensor error, power failure, low battery, high ambient, and door ajar alarms. Alarm mode is sound and flash. And the remote alarm interface is available.



### Configuration


Standard: 10-inch touch screen, RS485 interface, 2 coated steel wired shelves.

Optional: Temperature recorder, Printer, USB interface, NCF, IoT module, Stainless steel shelves, Blood basket.

**Product Parts**



**Product Dimension Drawings**



 **Specifications**

Model		DW-40L959BPT	
Technical Data	Cabinet Type	Upright	
	Climate Class	SNN	
	Cooling Type	Direct Cooling	
	Defrost Mode	Manual	
	Refrigerant	HC	
	Sound Level (dB(A))	42	
Performance	Cooling Performance (°C)	-40	
	Temperature Range(°C)	-20~-40	
Control	Controller	Microprocessor	
	Display	Touch screen LCD	
Electrical Data	Power Supply (V/Hz)	100~230/50/60	
	Capacity (L/Cu.Ft)	959/33.9	
Dimensions	Net/Gross Weight (approx)	(kg)	350/400
		(lbs)	771.6/881.8
	Interior Dimension (W*D*H)	(mm)	1016*716*1310
		(in)	40.0*28.2*51.6
	Exterior Dimension (W*D*H)	(mm)	1296*998*1980
		(in)	51.0*39.3*78.0
Packing Dimension (W*D*H)	(mm)	1358*1098*2127	
	(in)	53.5*43.2*83.7	
Container Load (20'/40'/40'H)		8/16/16	
Alarms	High/Low Temperature	Y	
	Remote Alarm	Y	
	Power Failure	Y	
	Sensor Error	Y	
	Low Battery	Y	
	High Ambient Temperature	Y	
	Dirty Condenser	N	
	Door Ajar	Y	
Accessories	Caster	Y	
	Leveling Feet	Y	
	Porthole	Y	
	Drawers/Inner Doors	N/3	
	Adjustable Shelves	Y (2)	
	USB Interface	Optional	
	RS485	Y	
	NFC	Optional	
Temperature Recorder	Optional		
Other	Certificate	CE, UL	

\*Haier Biomedical reserves the right to change products and specifications without prior notice.