

# Tabletop Low Speed Centrifuge

Old Model for TD5: TDZ5-WS

- · Microcomputer control, DC brushless motor, stable operation, low noise and high speed
- Touch panel, programmable operation, operation data can be set according to demands and stored automatically.
- LED or LCD display.user-friendly interface, simple and convenient operations.
- The real-time conversation of Speed and RCF is convenient for operation.
- It has self-locking device, lid safety device, over-speed safety device, and automatic alarm device, etc.
- · Silastic sealed ring comfort to GMP. US FDA certificated.

Model	TD5	
Max Speed	5000r/min	
Max RCF	4390xg	
Max Capacity	15mlx32	
Speed Accuracy	± 30r/min	
Time Setting	1min~99min	
Noise	<65dB(A)	
Power Supply	110V/60Hz, 220V/50Hz	
Dimension(LxWxH)	460mmx540mmx340mm	
Packing Size(LxWxH)	550mmx630mmx430mm	
Net Weight	28kg	



TD5 Tabletop Low Speed Centrifuge is widely used in the field of clinical medicine, biochemistry, genetic engineering, immunology, etc. It applies to hospitals, scientific research units, colleges and universities for centrifugal separation.



Rotor Capacity: 50mlx4 Max Speed: 5000r/min Max RCF: 4390xg



Adapter: 1.5mlx2x4 Adapter: 5ml/7mlx4 Adapter: 5mlx4 Vacuum Tube Adapter: 10mlx4 Adapter:15mlx4 Adapter: 20mlx4

No.2

Rotor Capacity: 50mlx8 Max Speed: 4000r/min Max RCF: 2810xg



Bucket

Adapter: 1.5mlx2x8 Adapter: 5ml/7mlx8 Vacuum Tube

Adapter: 5mlx8

Adapter: 15mlx8 Adapter: 20mlx8



Max Speed: 4000r/min Max RCF: 2810xg

15mlx4x4 Bucket 15mlx6x4 Bucket

15mlx8x4

Bucket

Adapter: 1.5ml Adapter: 1.5ml

Adapter: 10mlx8

Adapter: 1.5ml

Adapter: 5ml, 10ml

Adapter: 5ml 10ml

Adapter: 5ml 10ml


Adapter: 5ml/7m Vacuum Tube

Adapter: 5ml/7m Vacuum Tube

Adapter: 5ml/7m

Vacuum Tube

No.4



Rotor Capacity: 7mlx48 Max Speed: 4000r/min Max RCF: 2810xg



7mlx12x4 Bucket



