

Waterproof digital-calibrated thermometers



These digital thermometers measure the temperature of wet or dry environments including freezers, refrigerators, water baths, aquariums and incubators.

- Waterproof sensor
- Minimum/maximum temperature readings
- Dual-/triple-display with alarms

Probe length: 30 mm

Calibration points: 0; 50 °C

Individually serialised, CE marked, ISO/IEC 17025:2005

Includes accredited calibration documentation and multi-language instructions (English, French, German, Italian, Portuguese and Spanish) and supplied with AAA or LR44 (620-0919) battery.

* External

** Internal

Description	Range (°C)	Accuracy (°C)	Resolution (°C)	Probe	Cable length (m)	Pk	Cat. No.
With dual display and alarm with duration counter, W×H: 40×19 mm	-40...+70	±1,0	0,1	Waterproof sensor	1	1	620-2140
With backlit and max./min., W×H: 73×52 mm	-50...+70 * °C -10...+50 **	±1,0	0,1	Waterproof sensor	1	1	620-2199
With alarm and max./min., W×H: 90×44 mm	-50...+70 * °C -10...+50 **	±1,0	0,1	Waterproof sensor	1	1	620-0919
With solar power and max./min., W×H: 114×36 mm	-50...+70	±1,0	0,1	Waterproof sensor	1	1	620-1720